

# EnhanceLite™ PAR38

High output, PAR38 LED Lamp



EnhanceLite® PAR38

## Key Product Features

- High output PAR38 LED lamp
- Excellent color rendering
- Exceptional light distribution
- Enhanced passive cooling system allows for reduced junction temperatures, extending the life of the lamp
- Environmentally Friendly – No mercury, No lead & RoHS Compliant
- Maintenance free - Long life operation
- Integrated high efficiency driver
- Complies with ANSI standard PAR38 form factor
- All lamps are TÜV certified and tested to UL 1993, UL 8750 and are FCC certified
- No UV or IR radiation & No heat emitted in direction of light
- 5 year warranty

## Specification Data

| CCT (K)                  | Beam Angle | Power (W) | Lumens (lm) | CBCP (cd) | Efficacy (lm/W) | CRI | Voltage          | Base Type | Life (hrs) | Weight                | Dimmable | Model No.            |
|--------------------------|------------|-----------|-------------|-----------|-----------------|-----|------------------|-----------|------------|-----------------------|----------|----------------------|
| 2700K Incandescent White | 27°        | 13.5      | 760         | 2,645     | 56              | 83  | 90-135 VAC, 60Hz | E26       | 50,000     | 1 lb 0.4 oz (0.46 kg) | YES      | LED-PAR38-75-1XD-INF |
|                          |            | 19.0      | 950         | 3,550     | 50              |     |                  |           |            |                       |          | LED-PAR38-90-1XD-INF |
|                          | 35°        | 13.5      | 710         | 1,700     | 53              |     |                  |           |            |                       |          | LED-PAR38-75-1XD-IF  |
|                          |            | 19.0      | 870         | 2,285     | 46              |     |                  |           |            |                       |          | LED-PAR38-90-1XD-IF  |
|                          | 55°        | 13.5      | 710         | 735       | 53              |     |                  |           |            |                       |          | LED-PAR38-75-1XD-IWF |
|                          |            | 19.0      | 870         | 900       | 46              |     |                  |           |            |                       |          | LED-PAR38-90-1XD-IWF |
| 3000K Warm White         | 27°        | 13.5      | 760         | 2,645     | 56              | 83  | 90-135 VAC, 60Hz | E26       | 50,000     | 1 lb 0.4 oz (0.46 kg) | YES      | LED-PAR38-75-1WD-INF |
|                          |            | 19.0      | 950         | 3,550     | 50              |     |                  |           |            |                       |          | LED-PAR38-90-1WD-INF |
|                          | 35°        | 13.5      | 710         | 1,700     | 53              |     |                  |           |            |                       |          | LED-PAR38-75-1WD-IF  |
|                          |            | 19.0      | 870         | 2,285     | 46              |     |                  |           |            |                       |          | LED-PAR38-90-1WD-IF  |
|                          | 55°        | 13.5      | 710         | 735       | 53              |     |                  |           |            |                       |          | LED-PAR38-75-1WD-IWF |
|                          |            | 19.0      | 870         | 900       | 46              |     |                  |           |            |                       |          | LED-PAR38-90-1WD-IWF |
| 4000K Cool White         | 27°        | 13.5      | 882         | 3,068     | 65              | 80  | 90-135 VAC, 60Hz | E26       | 50,000     | 1 lb 0.4 oz (0.46 kg) | YES      | LED-PAR38-75-1CD-INF |
|                          |            | 19.0      | 1,102       | 4,118     | 58              |     |                  |           |            |                       |          | LED-PAR38-90-1CD-INF |
|                          | 35°        | 13.5      | 824         | 1,972     | 61              |     |                  |           |            |                       |          | LED-PAR38-75-1CD-IF  |
|                          |            | 19.0      | 1,009       | 2,651     | 53              |     |                  |           |            |                       |          | LED-PAR38-90-1CD-IF  |
|                          | 55°        | 13.5      | 824         | 852       | 61              |     |                  |           |            |                       |          | LED-PAR38-75-1CD-IWF |
|                          |            | 19.0      | 1,009       | 1,044     | 53              |     |                  |           |            |                       |          | LED-PAR38-90-1CD-IWF |

LEDnovation lamp models are tested for photometric performance in accredited third-party labs according to IES LM-79 requirements, with most reports available online at [www.lednovation.com](http://www.lednovation.com)

DESIGNED AND MANUFACTURED IN NORTH AMERICA

TESTED TO:  
**UL1993 & UL8750**



CERTIFICATION NUMBER:  
**U8 10 09 71814 003**

Represented by:

# HUDNUT LED LIGHTING

11916 NE SUMNER STREET PORTLAND, OREGON 97220 503-233-8088 INFO@HUDNUT.COM WWW.HUDNUT.COM