

EnhanceLite™ PAR20

High output, PAR20 LED Lamp



EnhanceLite® PAR20

Key Product Features

- High output PAR20 LED lamp
- Excellent color rendering
- Exceptional light distribution
- Enhanced passive cooling system allows for reduced junction temperatures, extending the life of the lamp
- Environmentally Friendly – No mercury, No lead & RoHS Compliant
- Maintenance free - Long life operation
- Integrated high efficiency driver
- Complies with ANSI standard PAR20 form factor
- All lamps are TÜV certified and tested to UL 1993, UL 8750 and are FCC certified
- No UV or IR radiation & No heat emitted in direction of light
- 5 year warranty

Specification Data

CCT (K)	Beam Angle	Power (W)	Lumens (lm)	CBCP (cd)	Efficacy (lm/W)	CRI	Voltage	Base Type	Life (hrs)	Weight	Dimmable	Model No.
2700K Incandescent White	27°	3.5	230	800	66	83	90-135 VAC, 60Hz	E26	50,000	6 oz (0.17 kg)	YES	LED-PAR20-35-1XD-INF
		5.9	372	1,300	63							LED-PAR20-50-1XD-INF
	35°	3.5	215	506	61							LED-PAR20-35-1XD-IF
		5.9	355	815	60							LED-PAR20-50-1XD-IF
	55°	3.5	210	217	60							LED-PAR20-35-1XD-IWF
		5.9	352	364	60							LED-PAR20-50-1XD-IWF
3000K Warm White	27°	3.5	230	800	66	83	90-135 VAC, 60Hz	E26	50,000	6 oz (0.17 kg)	YES	LED-PAR20-35-1WD-INF
		5.9	372	1,300	63							LED-PAR20-50-1WD-INF
	35°	3.5	215	506	61							LED-PAR20-35-1WD-IF
		5.9	355	815	60							LED-PAR20-50-1WD-IF
	55°	3.5	210	217	60							LED-PAR20-35-1WD-IWF
		5.9	352	364	60							LED-PAR20-50-1WD-IWF
4000K Cool White	27°	3.5	267	928	76	80	90-135 VAC, 60Hz	E26	50,000	6 oz (0.17 kg)	YES	LED-PAR20-35-1CD-INF
		5.9	432	1,508	73							LED-PAR20-50-1CD-INF
	35°	3.5	249	587	71							LED-PAR20-35-1CD-IF
		5.9	412	945	70							LED-PAR20-50-1CD-IF
	55°	3.5	244	252	70							LED-PAR20-35-1CD-IWF
		5.9	408	422	69							LED-PAR20-50-1CD-IWF

LEDnovation lamp models are tested for photometric performance in accredited third-party labs according to IES LM-79 requirements, with most reports available online at www.lednovation.com

DESIGNED AND MANUFACTURED IN NORTH AMERICA

TESTED TO:
UL1993 & UL8750



CERTIFICATION NUMBER:
U8 10 09 71814 003