

FULL CUT OFF LED WALL PACK



FIXTURE TYPE _____

JOB NAME _____

REP **HUDNUT LED LIGHTING**

PART NUMBER _____

SPECIFICATIONS

Manufactured in Portland, Oregon USA

Recommended installation height of 8-10 feet

Tempered clear glass lens

Proven reliability with high quality Cree brand emitters

50,000 hours of use to 70% of initial lumen output

Use of motion sensor will increase the life of the LEDs

Dimensions: Height = 10" Width = 14" Depth = 12"

Shipping weight: 6Lbs

Lumen output 2400 / 3600

Available with photocell and motion sensor

Internal multi-step thermal protection

Instant on LED's for better security lighting

UL approved

One year limited warranty

GSA contract item

Power factor = 0.94

ORDERING INFORMATION

<u>SERIES</u>	<u>LIGHT</u>	<u>BEAM</u>	<u>VOLTS</u>	<u>WATTS</u>	<u>MOUNTING</u>	<u>OPTIONS</u>
COMWP-HU	45 = 4500k	160	120	20	SM = Surface	PC = PHOTO CELL
			277	40		MS = MOTION SENSOR*
						HL = HALF LIGHT**

NOTES

**HL half light option operates fixture at half output until motion is detected when fixture goes to full light output for a field selectable period of time.

***Contact Hudnut for additional options available

All values are nominal. Product may differ slightly from photo.

HUDNUT LED LIGHTING

11916 NE SUMNER STREET PORTLAND, OREGON 97220 503-233-8088 WWW.HUDNUT.COM INFO@HUDNUT.COM

MEDIUM WALL PACK



FIXTURE TYPE _____

JOB NAME _____

REP **HUDNUT LED LIGHTING**

PART NUMBER _____

SPECIFICATIONS

Manufactured in Portland, Oregon USA	Lumen output 2400 / 3600
Recommended installation height of 10 feet	For indoor or outdoor use
Glass prism lens cover	Internal multi-step thermal protection
Proven reliability with genuine Cree brand emitters	Available with photocell and motion sensor
50,000 hours of use to 70% of original lumen output	UL Approved
Use of motion sensor will increase the life of the LEDs	One year limited warranty
Dimensions: Height = 10" Width = 14" Depth = 12"	GSA contract item
Shipping weight: 6Lbs	Power factor = 0.94

ORDERING INFORMATION

<u>SERIES</u>	<u>LIGHT</u>	<u>BEAM</u>	<u>VOLTS</u>	<u>WATTS</u>	<u>MOUNTING</u>	<u>OPTIONS</u>
MWP-HU	45 = 4500k	160	120 277	20 40	SM = Surface	PC = PHOTO CELL MS = MOTION SENSOR HL = HALF LIGHT OPTION**

NOTES

**HL half light option operates fixture at half output until motion is detected when fixture goes to full light output for a field selectable period of time.

***Contact Hudnut for other available options.

All values are nominal

Product may differ slightly from photo.

HUDNUT LED LIGHTING