

# LED ROADWAY & AREA LIGHT



FIXTURE TYPE \_\_\_\_\_

JOB NAME \_\_\_\_\_

REP **HUDNUT LED LIGHTING**

PART NUMBER \_\_\_\_\_

## SPECIFICATIONS

IP65 water resistant rated

UL listed

Type I and Type II beam spreads available

Modular design allows a wide range of light outputs

All aluminum housing

LED efficiencies are 150 Lm/W minimum

Operates in negative 40 to plus 122 degrees F. ambient air temp.

50,000 hour rated to 70% light output

3 year manufacturer warranty

CRI 75 minimum

72w = 22" L x 16" W x 5.25" D 5,400 lumens

145w = 31" L x 16" W x 5.25" D 10,800 lumens

220w = 37.5" L x 16" W x 5.25" D 16,500 lumens

Power factor >0.95

IES file and photometric report available

Maximum 2.44" O.D. pole fitter

## ORDERING INFORMATION

<u>SERIES</u>	<u>LIGHT</u>	<u>BEAM</u>	<u>VOLTS</u>	<u>WATTS</u>	<u>MOUNTING</u>	<u>OPTIONS</u>
RWU-UN	3500K	TYPE I	100-240VAC	72w	PM = pole mount	PC = photo cell
	4500K	TYPE II	277VAC	145w		***
	6500K			220w		

## NOTES

\*\*\*Other options may be available. Contact Hudnut LED Lighting Solutions for additional information.

All values are nominal.

Product may differ slightly from photo

# HUDNUT LED LIGHTING

11916 NE SUMNER STREET PORTLAND, OREGON 97220 503-233-8088 WWW.HUDNUT.COM INFO@HUDNUT.COM